

日東コン 材質 B (チタン酸バリウム系) 規格表

形式名	端子構造	静電容量 [pF] ±50%	直流電圧 (常温)		寸法 (mm)			備考
			定格 [kV]	試験電圧 [kV]	D±10%	T	H	
BE-60	S	20,000	4	8	60	1~4	20~23	
BE-60	S	10,000	5	10	60	4~8	23~27	
BE-60	S	5,000	6	12	60	5~9	24~28	
BE-50	S	15,000	2.5	5	50	1~4	20~23	
BE-50	S	8,000	3	6	50	2~6	21~25	
BE-50	S	5,000	4	8	50	2~7	21~26	
BE-50	S	3,000	5	10	50	3~7	22~26	
BE-50	S	2,000	5	10	50	3~7	22~26	
BE-40	S	10,000	2.5	5	40	1~4	20~23	
BE-40	S	5,000	3	6	40	1~5	20~24	
BE-40	S	3,000	4	8	40	1~5	20~24	
BE-40	S	2,000	4	8	40	2~6	21~25	
BE-40	S	1,000	4	8	40	2~6	21~25	
BE-30	S-L	10,000	1	2	30	0.5~3	19~22	
BE-30	S-L	5,000	2	4	30	1~4	20~23	
BE-30	S-L	3,000	3	6	30	1~5	20~24	
BE-30	S-L	2,000	3	6	30	1~5	20~24	
BE-30	S-L	1,000	3	6	30	1~5	20~24	
BE-20	S-L	2,000	2	4	20	1~5	16~20	
BE-20	S-L	1,000	2	4	20	1~4	16~19	