

# 日東コン 材質 R (酸化チタン系) F 型 規格表

形式名	端子構造	公称 静電容量 pF±10%	定格電圧		定格 KVA (1MHz)		最大値			寸法 (mm)			備考
			50°C kV <sub>DC</sub>	70°C kV <sub>DC</sub>	50°C	70°C	HF kV	電流 [A]		D ±10%	T ±3	H ±3	
								50°C	70°C				
RDF200C-S	S	500	25	20	300	200	30	55	46	200	47.0	79.0	T・H 寸法 公差±8
RDF200C-S	S	1000	25	20	300	200	30	60	55	200	35.0	67.0	
RDF200C-S	S	1500	25	20	180	120	30	62	56	200	29.0	61.0	
RDF200C-S	S	2000	20	17	180	120	25	63	57	200	26.0	58.0	
RF-140	S	500	25	20	90	60	30	30	25	140	25.0	52.0	
RF-140	S	600	25	20	90	60	30	32	26	140	23.0	50.0	
RF-140	S	700	25	20	90	60	30	33	27	140	24.0	51.0	
RF-140	S	800	25	20	90	60	30	34	28	140	24.0	51.0	
RF-140	S	1000	21	17	90	60	25	35	30	140	22.0	49.0	
RF-140	S	1500	13	10	90	60	15	30	25	140	19.0	46.0	
RF-140	S	2000	8	7	67.5	45	9	35	30	140	18.0	45.0	
RF-140	S	2500	7	6	67.5	45	7	35	30	140	17.0	44.0	
RF-110	S	200	20	17	45	30	25	18	15	110	30.0	57.0	
RF-110	S	300	25	20	90	60	30	25	20	110	27.0	54.0	
RF-110	S	400	25	20	90	60	30	26	21	110	25.0	52.0	
RF-110	S	500	13	11	30	20	16	21	17	110	18.0	49.0	
RF-110	S	600	15	12	30	20	18	22	18	110	18.5	47.0	
RF-110	S	700	12	10	30	20	14	22	18	110	17.5	46.0	
RF-110	S	800	12	10	30	20	14	26	18	110	17.5	45.0	
RF-110	S	1000	10	8	30	20	12	25	20	110	15.0	44.0	
RF-110	S	1200	8	7	22	14	10	25	20	110	14.5	44.0	
RF-110	S	1500	8	7	22	14	10	25	20	110	14.0	43.5	
RF-110	S	2000	7	6	22	14	7	25	20	110	13.5	43.0	
RF-110	S	2500	5	4	22	14	5	25	20	110	13.0	42.0	
RF-80	S	100	13	11	22	14	16	13	11	80	26.5	40.0	
RF-80	S	150	13	11	22	14	16	13	11	80	26.5	40.0	
RF-80	S	200	15	12	30	20	18	16	13	80	20.5	33.5	
RF-80	S	250	15	12	30	20	18	16	13	80	19.0	32.0	
RF-80	S	300	15	12	30	20	18	17	14	80	17.5	30.5	
RF-80	S	400	12	10	15	10	14	16	13	80	16.0	29.0	
RF-80	S	500	12	10	15	10	14	16	13	80	15.0	28.5	
RF-80	S	600	10	8	15	10	12	17	14	80	14.5	27.5	
RF-80	S	700	10	8	15	10	12	18	15	80	13.8	27.5	
RF-80	S	800	8	7	15	10	9	18	15	80	13.8	27.0	
RF-80	S	1000	8	7	15	10	9	18	15	80	13.5	27.0	
RF-80	S	1200	6	5	15	10	7	18	15	80	12.8	26.5	
RF-80	S	1500	5	4	10	8	6	18	15	80	12.5	26.0	
RF-60	S	100	12	10	15	10	14	10	8	60	22.0	31.0	
RF-60	S	150	12	10	15	10	14	11	9	60	19.0	30.0	
RF-60	S	200	12	10	15	10	14	12	10	60	18.0	28.5	
RF-60	S	250	12	10	15	10	14	12	10	60	18.0	27.5	
RF-60	S	300	10	8	7.5	5	12	12	10	60	16.5	26.0	
RF-60	S	400	10	8	7.5	5	12	12	10	60	15.5	25.5	
RF-60	S	500	6	5	7.5	5	7	13	11	60	14.0	24.0	
RF-60	S	600	6	5	7.5	5	7	13	11	60	13.5	23.5	
RF-60	S	700	6	5	7.5	5	7	13	11	60	13.5	23.0	
RF-60	S	800	5	4	7.5	5	6	13	11	60	13.5	23.0	
RF-60	S	1000	5	4	7.5	5	6	13	11	60	12.5	22.0	
RF-40	S	50	10	8	6	4	12	6	5	40	21.5	35.0	
RF-40	S	100	10	8	6	4	12	7	6	40	19.0	28.0	
RF-40	S	150	10	8	6	4	12	8	7	40	13.5	25.0	
RF-40	S	200	5	4	4.5	3	6	8	7	40	13.2	23.5	
RF-40	S	250	5	4	4.5	3	6	8	7	40	13.2	22.5	
RF-40	S	300	5	4	4.5	3	6	9	8	40	13.2	22.5	
RF-30	S	50	5	4	3	2	6	5	4	30	15.0	28.0	
RF-30	S	100	5	4	3	2	6	6	5	30	12.0	23.5	
RF-30	S	150	5	4	3	2	6	7	6	30	10.0	23.0	
RF-30	S	200	4	3	3	2	5	7	6	30	10.0	22.0	