

日東コン 材質 S (ステアタイト系) F 型 規格表

形式名	端子構造	公称 静電容量 pF±10%	定格電圧		定格 KVA (1MHz)		最大値			寸法 (mm)			備考
			50°C kV _{DC}	70°C kV _{DC}	50°C	70°C	HF kV	電流 [A]		D ±10%	T ±3	H ±3	
								50°C	70°C				
SDF160C-S	S	50	34	27	135	90	36	18	15	160	38.0	54.0	
SDF160C-S	S	100	32	25	135	90	31.5	22	18	160	34.0	50.0	
SDF160C-S	S	150	30	24	90	60	30	22	18	160	30.0	46.0	
SDF160C-S	S	200	27	21	90	60	27	24	20	160	29.0	45.0	
SDF140C-S	S	50	34	27	90	60	31.5	17	14	140	33.0	51.0	
SDF140C-S	S	100	32	25	90	60	30	20	17	140	32.0	49.0	
SDF140C-S	S	150	30	24	60	40	27	20	17	140	30.0	46.0	
SDF140C-S	S	200	24	19	60	40	24	22	18	140	28.0	44.0	
SDF110C-S	S	40	28	22	67.5	45	26	13	11	110	28.0	51.0	
SDF110C-S	S	50	28	22	67.5	45	26	15	12	110	30.0	50.0	
SDF110C-S	S	60	24	19	67.5	45	22	15	12	110	24.0	48.0	
SDF110C-S	S	70	24	19	67.5	45	22	16	13	110	23.5	47.0	
SDF110C-S	S	80	24	19	45	30	22	16	13	110	22.5	46.0	
SDF110C-S	S	100	24	19	45	30	22	16	13	110	25.0	45.0	
SDF110C-S	S	150	18	14.5	45	30	16	17	14	110	24.0	44.0	
SDF80C-S	S	20	25	20	45	30	23	10	8	80	31.5	38.5	
SDF80C-S	S	25	25	20	45	30	23	10	8	80	29.0	36.0	
SDF80C-S	S	30	25	20	45	30	23	10	8	80	27.5	34.5	
SDF80C-S	S	40	23	18.5	30	20	21	10	8	80	25.0	32.0	
SDF80C-S	S	50	23	18.5	30	20	21	11	9	80	23.5	30.5	
SDF80C-S	S	60	18	14.5	22.5	15	16	11	9	80	23.0	29.5	
SDF80C-S	S	70	18	14.5	22.5	15	16	11	9	80	22.0	29.0	
SDF80C-S	S	80	18	14.5	22.5	15	16	11	9	80	21.5	28.5	
SDF80C-S	S	100	18	14.5	22.5	15	16	12	10	80	20.5	27.5	
SDF60C-S	S	10	20	17	22.5	15	19	6	5	60	19.5	31.0	
SDF60C-S	S	15	20	17	22.5	15	19	7	6	60	20.0	31.0	
SDF60C-S	S	20	20	17	22.5	15	19	7	6	60	15.5	27.0	
SDF60C-S	S	25	18	14.5	15	10	16	7	6	60	14.5	26.0	
SDF60C-S	S	30	18	14.5	15	10	16	7	6	60	14.0	25.0	
SDF60C-S	S	40	18	14.5	15	10	16	8	7	60	12.0	23.5	
SDF60C-S	S	50	14	11	11	7.5	12	8	7	60	11.5	23.0	
SDF60C-S	S	60	14	11	11	7.5	12	8	7	60	11.0	22.5	
SDF60C-S	S	70	10	8	11	7.5	10	8	7	60	10.5	22.0	
SDF60C-S	S	80	10	8	11	7.5	10	8	7	60	10.0	21.5	
SDF40C-S	S	5	14	11	7.5	5	12	5	4	40	16.0	28.5	
SDF40C-S	S	10	14	11	7.5	5	12	5	4	40	16.0	27.5	
SDF40C-S	S	15	14	11	7.5	5	12	5	4	40	14.5	25.0	
SDF40C-S	S	20	14	11	7.5	5	12	5	4	40	12.0	23.5	
SDF40C-S	S	25	14	11	7.5	5	12	6	5	40	11.5	23.0	
SDF40C-S	S	30	14	11	7.5	5	12	6	5	40	10.5	22.5	
SDF30C-S	S	5	8	7	4.5	3	6	3.7	3	30	15.0	27.5	
SDF30C-S	S	10	8	7	4.5	3	6	5	4	30	12.0	23.5	
SDF30C-S	S	15	8	7	4.5	3	6	5	4	30	11.0	22.5	